

SET-UP SHEET

X4'23 SET-UP SHEET VER.1 ©XRAY

XRAY X4'23

RACE			
TRACK			
NAME		DATE	

QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
		/sec	/	

TRACK			
TRACK SURFACE	☐ CARPET	☐ ASPHALT	
TRACK LAYOUT	☐ TECHNICAL	☐ MIXED	☐ FAST
TRACTION	☐ LOW	☐ MEDIUM	☐ HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	☐ FRONT SOLID AXLE	GEAR DIFF OIL
PINION	SPUR GEAR	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
	XRAY SPRINGS	
	OIL /Cst	
	REBOUND %	
☐ YES ☐ NO	FOAM INSERTS	☐ YES ☐ NO

☐ 4 HOLES	1.1mm	1.1mm	☐ 4 HOLES
☐ PSS	1.2mm	1.2mm	☐ PSS
SHOCK LENGTH	/mm	/mm	SHOCK LENGTH

ANTI-ROLL BAR	
THICKNESS/mm	THICKNESS/mm

TIRES	
ADDITIVE	
ADDITIVE TIMING	

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT
------------	-------------	--------------	-----------	------------

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT %	REAR %
--------------	----	----------------	---------	--------

MOTOR	TIMING
ESC	BATTERIES
BODY	WING

	BODY POSITION Dimension from body post to window bottom line /mm WING SIDE PLATE YES ☐ NO ☐ Dimension from edge to surface /mm
--	--

	1.6mm ☐ 2.0mm ☐ 1.6mm 2.0mm ☐ 1.6mm NONE ☐ BEARING ☐
--	---

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER 5° 4° 3° Adjust with eccentric bushings UPPER CLAMP STD. ☐ -1.5mm	REAR CASTER 0.5° 1.5° 2.5° 3.5° 4.5° 5.5° Adjust with eccentric bushings UPPER CLAMP STD. ☐ -1.5mm
BUMP STEER /mm HEIGHT /mm SHIM /mm RIDE HEIGHT /mm SERVO SAVER SERVO HORN	TOE GAIN /mm RIDE HEIGHT /mm

CAMBER /degr. Left = Right BODY STOP YES ☐ NO ☐ /mm DRIVE SHAFT 58mm 59mm BEARING BLADE #107702 Chassis Droop Gauge Blocks	FRONT SUSPENSION FRONT BRACE YES ☐ NO ☐ BULKHEAD SHIMS YES ☐ 3mm ☐ NO SHIM /mm FRONT HUB HARD ☐ GRAPHITE ☐ ALU ☐ SHIM /mm DOWNSTOP /mm
--	---

CAMBER /degr. Left = Right BODY POST VERTICAL ☐ HORIZONTAL ☐ DRIVE SHAFT 52mm 54mm BEARING BLADE #107702 Chassis Droop Gauge Blocks	REAR SUSPENSION SHIM /mm REAR SHOCK POSITION 1 2 SHIM /mm REAR HUB HARD ☐ GRAPHITE ☐ ALU ☐ SHIM /mm DOWNSTOP /mm
---	--

TOE OUT Left = Right DIFF POSITION UP ☐ DOWN ☐ UPPER ARM SOFT ☐ MEDIUM STD. ☐ HUB OFFSET STD. ☐ -0.5mm ☐ +0.5mm SHIM/mm	ACKERMANN SHIM /mm STEERING BRIDGE YES ☐ NO ☐ STEERING PLATE 8.0mm ☐ STD. ☐ 7.5mm ☐	TOE IN Left = Right SHIM /mm DIFF POSITION UP ☐ DOWN ☐ UPPER ARM SOFT ☐ MEDIUM STD. ☐ HUB OFFSET STD. ☐ -0.5mm ☐ +0.5mm SHIM/mm
---	---	---

FRONT BOTTOM VIEW STEER. LOCK /degr. STEER. SHIM /mm FRONT BRACE YES ☐ NO ☐ FRONT ARMS MEDIUM ☐ HARD ☐	REAR T-BRACE ALU ☐ BRASS ☐ REAR ARMS MEDIUM ☐ HARD ☐
--	---