

SET-UP SHEET

XB2'24 SET-UP SHEET VER. 1 ©XRAY 2023

XRAY XB2'24

RACE		
TRACK		
NAME	DATE	

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK		
SIZE	☐ OPEN	☐ MEDIUM
TRACTION	☐ VERY-LOW ☐ MEDIUM ☐ VERY-HIGH	
SURFACE	☐ SMOOTH	☐ MEDIUM
TYPE	☐ CLAY	☐ CARPET
CONDITION	☐ BLUE GROOVE	☐ HARD PACKED
	☐ DUSTY	☐ LOAMY

TRANSMISSION		
BALL DIFF	☐	GEAR DIFF
DIFFERENTIAL	OIL	ACTIVE DIFF
SATELLITE GEARS	COMPOSITE	STEEL
SLIPPER	mm	NUT
SOLID AXLE	☐	2-PAD SLIPPER CLUTCH PLATES
	KIT	VENTILATED

GEARING		
PINION	T	SPUR GEAR
TYPE	GEAR BOX	
FRONT LCG	REAR LCG	HARDNES
	KIT	GRAPHITE

FRONT	SHOCKS	REAR
SPRINGS		
OIL		
2 HOLES	☐	2 HOLES
HOLES	mm	HOLES
Thickness	2.0mm	2.0mm
Precision	KIT	Precision
DOWNSTOP SHIM	mm	DOWNSTOP SHIM
LENGTH	mm	LENGTH
UPSTOP SHIM	mm	UPSTOP SHIM
KIT	0mm	KIT
ALU	-2mm	ALU
	-4mm	
COLLAR		
BALL JOINT		

FRONT	ANTI ROLL BAR	REAR
THICKNESS		

FRONT	TIRES	REAR
BRAND		
COMPOUND		
INSERTS		
WHEELS		

ELECTRONICS		
MOTOR		SPEEDO
MOTOR TIMING		BATTERY

BODY	☐ LIGHT	TOTAL WEIGHT
		/g

COMMENT

FRONT	APPLIED	REAR
CASTER BLOCK MEDIUM - KIT ☐ HARD ☐ GRAPHITE ☐ ALU ☐ ALU C-HUB ☐ UP /mm DOWN /mm	LONGER BUSHINGS UP ☐ DOWN ☐	SHOCK TOWER KIT ☐ 4.0mm 3.5mm
STEERING BLOCK MEDIUM - KIT ☐ HARD ☐ GRAPHITE ☐ ALU ☐	SHIM /mm CAMBER LINK LOCATION	SHIM /mm DRIVE SHAFT ☐ KIT /mm SHIM /mm STANDARD ARM ☐ 1 2 DISENGAGED ARM ☐ 1 2 3 #325341 ADJ. DRIVE AXLE

ARM MOUNT 0° ☐ KIT 0° ☐ ALU -3° ☐ ALU +3° ☐ ALU 0° ☐ BRASS TOTAL ☐ KICK-UP°	FRONT WING YES ☐ NO ☐ KIT ☐ OTHER ☐ SHIM /mm ACKERMANN SHIM /mm CASTER BUSHINGS 0° 2.5° 5° ARM MOUNT 0° + CASTER BUSHING 0° = TOTAL 22° KICK-UP	WING TYPE CENTER FIN YES ☐ NO ☐ WING POSITION UP ☐ MIDDLE ☐ DOWN ☐
--	---	---

FRONT TOE OUT ☐ OFFSET /slots WHEELBASE /mm ROLL CENTER KIT ☐ ALU ☐ STEERING PLATE KIT ☐ ALU ☐ ARMS KIT ☐ ALU ☐	EXTENSION 1 DOT ☐ 2 DOTS ☐ 3 DOTS ☐	BATTERY PLACEMENT LONG SIDE FRONT ☐ LONG SIDE REAR ☐ SERVO POSITION 1 2 BATTERY SIZE STD. SHORT ☐ LOW SHORT ☐ UPPER BRACE YES ☐ NO ☐ COOLING FRONT ☐ REAR ☐	REAR TOE IN ☐ OFFSET /slots WHEELBASE /mm ROLL CENTER KIT ☐ GRAPHITE ☐ ALU ☐
---	--	---	---

REAR ROLL CENTER SUSPENSION HOLDERS RF 0.5° ☐ 1° ☐ RR 0.5° ☐ 1° ☐	#323326 ALU REAR LOWER SUSPENSION HOLDER 1° - REAR Raising the suspension holders with shims.
--	---

FRONT CAMBER GLUING SIDEWALL YES ☐ NO ☐ FRONT ARM MEDIUM ☐ HARD ☐ GRAPHITE ☐	DIFF HEIGHT #107721 GAUGE	REAR CAMBER CUTTING PINS IN ☐ OUT ☐ NO ☐ NO ☐ REAR ARM MEDIUM ☐ HARD ☐ GRAPHITE ☐
---	-------------------------------------	--

SERVO WEIGHT STANDARD ☐ LOW PROFILE ☐	LOWER ECCENTRIC SHOCK BALL FRONT ☐ REAR ☐	ARM SHIM /mm CHASSIS SIZE SHORT ☐ MID-SIZE ☐ LONG ☐ THICKNESS 2.5mm KIT ☐ 2.0mm ☐
--	---	--