

SETUP SHEET



EVENT			
TRACK			
DRIVER		DATE	
QUALIFY		FINAL	
BEST LAP		LAP / TIME	
TEMP. AIR		TEMP. TRACK	

TRACK

SURFACE	☐ ASPHALT	☐ CARPET	
LAYOUT	☐ TECHNICAL	☐ MIXED	☐ FAST
TRACTION	☐ LOW	☐ MEDIUM	☐ HIGH

TRANSMISSION

FRONT		REAR	
DIFF OIL		☐ SOLID AXLE	
PULLEY		☐ 38/20T ☐ 40/22T ☐ STD. ☐ LOW FRICTION	
PINION	T	SPUR	T
		FDR	

SHOCKS

FRONT		REAR	
MEMBRANE	☐ HARD ☐ SOFT ☐ SOFT V2	☐ HARD ☐ SOFT ☐ SOFT V2	
SPRINGS			
OIL			
REBOUND (%)			
PISTONS			
LENGTH	mm	mm	
STABILIZER		mm	

TIRES

FRONT		REAR	
TIRES			
ADDITIVE			
TIMING			
WARMERS	Temp.	Timing	Temp.
			Timing

ELECTRONICS

MOTOR		TIMING	
ESC		BATTERY	

WEIGHT & BALANCE

WEIGHT	g	BALANCE	FRONT	%	REAR	%
--------	---	---------	-------	---	------	---

BODY

BODY		WING	
------	--	------	--

BODY POSITION

Dimension from body post to windows bottom line
 mm

Dimension from body post to upper holder
 mm

SIDE PLATE
☐ YES ☐ NO

Dimension from edge to surface
 mm

TOP DECK

☐ 1.6mm ☐ 2.0mm ☐ 1.6mm ☐ 2.0mm

☐ Screws ☐ Shims

TOP DECK CUTTING

COMMENTS

FRONT

CASTER deg.
 BUMP STEER mm
 SHIM mm
 HEIGHT mm
 FF SHIM mm
 RIDE HEIGHT mm
 FR SHIM mm
 SERVO HORN
☐ ALU.
☐ STD.

REAR

TOE GAIN mm
 CASTER deg.
 RF SHIM mm
 RIDE HEIGHT mm
 RR SHIM mm

FRONT

CAMBER deg.
 BODY STOP
☐ YES ☐ NO
 SHIM mm
 SHOCK SHIM mm
 SHIM mm
 FRONT HUB
☐ GRAPHITE
☐ HARD
 DROOP mm
☐ Set with shocks
☐ Set without shocks
 SHIM mm
 BULK BRACE
☐ YES ☐ NO
 SHOCK SHIM mm

REAR

CAMBER deg.
 BODY POST
☐ VERTICAL
☐ HORIZONTAL
 SHIM mm
 SHOCK SHIM mm
 SHIM mm
 REAR HUB
☐ GRAPHITE
☐ HARD
 DROOP mm
☐ Set with shocks
☐ Set without shocks
 SHIM mm
 BULK BRACE
☐ YES ☐ NO
 SHOCK SHIM mm

TOE deg.
 ACKERMANN mm
 TOE IN deg.
 CENTER WEIGHT
☐ 14g ☐ 10g
 DIFF POSITION
☐ UP
☐ DOWN
 HUB
☐ +0.5mm
☐ STD.
☐ -0.5mm
 SHIM mm
 STEER PLATE
☐ 8.5mm
☐ 8.0mm(STD)

STEER. LOCK deg.
 MOTOR MOUNT
 CHASSIS
☐ GRAPHITE
☐ ALU 2.0mm
 FRONT ARMS
☐ HARD
☐ STD.
 REAR ARMS
☐ HARD
☐ STD.