

SETUP SHEET

V. 1.2 - UPPER LINKS

ENGINE **Ultimate M3X 2.0**

PLUG **OS P3**

PIPE **Ultimate 2141**

FUEL **Nitrolux 25%**

CLUTCH **Mayako 3 shoe**

CLUTCH SHOES **Mayako**

CLUTCH SPRINGS **2x 1.0, 1x1.1**

RUNTIME **~6mins**

FRONT DIFF OIL **20**

CENTER DIFF OIL **10**

REAR DIFF OIL **6**

OIL QUANTITY(gr) **2.7**

OIL QUANTITY(gr) **6**

OIL QUANTITY(gr) **2.7**

DIFF GEAR **45**

DIFF PINION **14**

SPUR GEAR **48**

CLUTCH BELL **13**

SHOCKS

	FRONT	REAR
OIL	650	650
PISTON	7x1.3	7x1.4
SPRING	Black Linear	Black Linear
LENGTH	103	120
VISIBLE SHAFT LENGTH		
REBOUND	Min	Min
FRONT SHOCK END	☐ LONG ☒ SHORT	SHOCKS ☒ EMULSION TYPE ☐ BLADDER
NOTES		

FRONT END

SHOCK TOWER ☒ ALUMINIUM ☐ CARBON

HEX WIDTH ☒ 4 mm ☐ 5 mm ☐ 6 mm

KNUCKLE PLATE ☒ 1 LONG ☐ 2 SHORT

FRONT ARM POSITION ☐ FRONT ☒ MIDDLE ☐ REAR

ARM INSERT ☐ NO ☒ PLASTIC ☐ CARBON

KNUCKLE POSITION ☐ UP ☒ MIDDLE ☐ DOWN

KPI OPTION ☒ KPI 0 (ROUND MARK) ☐ KPI 1 (LONG MARK)

C BLOCK CASTER ☐ CASTER 1 (1 MARK) ☒ CASTER 2 (2 MARKS)

SERVO SAVER ☐ YES ☒ NO

BUMP STEER ON ACKERMAN ☒ UP ☐ DOWN SHIM **2** mm

BUMP STEER ON KNUCKLE ☒ UP ☐ DOWN SHIM **1** mm

KICK UP: 1 ☐ 0.5 ☐ 0 ☐ 0.5 ☒ 1 ☐

A PLATE: ☐ +2mm SHIM (NO upper gearbox shim) ☐ +2mm SHIM ☐ +1mm SHIM (1mm upper gearbox shim) ☒ +1mm SHIM ☐ NO SHIM (2mm upper gearbox shim)

B PLATE: ☐ +2mm SHIM ☐ +1mm SHIM ☐ NO SHIM

TOWER: ☐ +2mm SHIM ☐ +1mm SHIM ☐ NO SHIM

CHASSIS

	FRONT	REAR
CAMBER	-1	-2
RIDE HEIGHT	25	27
DOWNTRAVEL (WITH TYRES)		
DOWNTRAVEL (on 36mm blocks)		
ANTI ROLL BARS	2.3	2.6
BRAKE BALANCE	50	50
ENGINE MOUNT	☐ FORWARD (+2mm) ☐ SHORT ☐ BACKWARD (-2mm) ☐ LONG	
THROTTLE	☐ SHORT ☐ LONG	
SERVO MOUNT	☐ LONG	WEIGHT

TYRES

	FRONT	REAR
BRAND	Procircuit	Procircuit
TREAD	Addictive	Addictive
COMPOUND	C3	C3
WHEELS	Procircuit	Procircuit
INSERTS	Procircuit	Procircuit
GLUED TO WHEEL	☐ YES ☒ NO	☐ YES ☒ NO

REAR END

ARM INSERT ☐ NO ☒ PLASTIC ☐ CARBON

SHOCK TOWER ☒ ALUMINIUM ☐ CARBON

HEX WIDTH ☐ 4 mm ☒ 5 mm ☐ 6 mm

SPACER IN FRONT OF HUB **2** mm

REAR AXLE CVD ☒ UNIVERSAL ☐ 91 ☐ 94

REAR HUB ☒ PLASTIC ☐ ALUMINIUM

OPTIONAL REAR HUB: 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6

ANTI-SQUAT: 1 ☐ 0.5 ☐ 0 ☐ 0.5 ☒ 1 ☐

C PLATE: ☐ +2mm SHIM ☐ +1mm SHIM ☐ NO SHIM

D PLATE: ☐ +2mm SHIM ☐ +1mm SHIM ☐ NO SHIM

TOWER: ☐ +2mm SHIM ☐ +1mm SHIM ☐ NO SHIM

RADIO SETTINGS

	THROTTLE	STEERING
DUAL RATE		0
SPEED		
EXPO	None	None
SERVO MODEL		
THROTTLE		BRAKE
ELECTRIC EPA		

BODY & WING

BODYSHELL	Mayako
WING BRAND	Mayako
WING MODEL	Grey
WING POSITION	☐ 1 ☐ 2 ☒ 3 ☐ 4
	1 IS FRONT HOLE (WING BACK)
WING FLAPS	☐ BIG ☐ SMALL ☐ BOTH
GURNEY	☒ NO ☐ SMALL ☐ BIG

NOTES

Links front and rear