

Name:	Date:	Event:	Track:
Track Conditions		Setup: RC Excitement	
☐ Indoor	☐ Clay	☐ Carpet	☐ Tight
☐ Outdoor	☐ Dirt	☐ Astro	☐ Open
☐ Smooth	☐ Hard Packed	☐ Blue Groove	☐ Wet
☐ Rough	☐ Loose/Loamy	☐ Dry	☐ Dusty
Bite: ☐ Low ☐ Med ☐ High		Tread: ☐ Pin ☐ Ghost ☐ Slicks	

[Open in So Dialed App](#)

Front Suspension	<table border="1"> <tr> <td>Ride Height</td> <td>mm</td> </tr> <tr> <td>Camber</td> <td>°</td> </tr> <tr> <td>Toe</td> <td>°</td> </tr> <tr> <td>Sway Bar</td> <td>mm</td> </tr> <tr> <td colspan="2">Notes:</td> </tr> </table>	Ride Height	mm	Camber	°	Toe	°	Sway Bar	mm	Notes:		mm Spacer ☐ Composite ☐ Aluminum ☐ Composite ☐ Aluminum ☐ Standard ☐ Low Mount ☐ 2mm ☐ 3mm ☐ 4mm ☐ 1.0 ☐ 0.5 ☐ 0.0 ☐ 4 ☐ 5 ☐ 6 ☐ 0° ☐ 5° B A ☐ Composite ☐ Carbon Std ☐ Carbon +2mm 3 2 1 mm Spacer 3 2.5 2 1.5 1 mm Spacer ☐ Long ☐ Short Outside Middle Inside ☐ 1mm ☐ 2mm ☐ 3mm ☐ 20° ☐ Composite ☐ Aluminum ☐ Brass + g ☐ HRC ☐ 30°
Ride Height	mm											
Camber	°											
Toe	°											
Sway Bar	mm											
Notes:												

Rear Suspension	<table border="1"> <tr> <td>Ride Height</td> <td>mm</td> </tr> <tr> <td>Camber</td> <td>°</td> </tr> <tr> <td>Sway Bar</td> <td>mm</td> </tr> <tr> <td colspan="2">Notes:</td> </tr> </table>	Ride Height	mm	Camber	°	Sway Bar	mm	Notes:		mm Spacer ☐ Composite ☐ Aluminum 2 Laydown 1 3 2 Standup ☐ 67mm ☐ 68mm ☐ X67mm ☐ X68mm Shock Location ☐ Front ☐ Rear mm Spacer mm Spacer Outside Middle Inside ☐ 0 ☐ +1.0 ☐ +1.75 ☐ +2.5 ☐ +3.5 ☐ +1 ☐ 0 ☐ -1 ☐ 4.5 ☐ 5.0 ☐ 5.5 ☐ 6.0 ☐ Std 0 +1 +2 +3 +4 ☐ 2mm ☐ 3mm ☐ 4mm ☐ 1.0 ☐ 0.5 ☐ 0.0 ☐ 4 ☐ 5 ☐ 6 ☐ 0° ☐ 5° B A C
Ride Height	mm									
Camber	°									
Sway Bar	mm									
Notes:										

Chassis	Drive Train
Diff Type	☐ Ball Diff ☐ Gear Diff
Setting/Fluid	
Internal Gears	☐ Steel ☐ Composite
Planet Gears	☐ 2 ☐ 4
Slipper	
Slipper Pads	☐ Torque/Yellow ☐ Drive/Orange

Aerodynamics
Body
Fr Wing
Rr Wing
Wicker
Angle
Notes

Tires	Front	Rear
Brand		
Tread		
Compound		
Insert		
Sauce		
Wheel		
Notes		

Shocks	Front	Rear
Shock Caps		
Oil		
Piston		
Limiter, Int	mm	mm
Shaft Dia	☐ 3.0mm ☐ 3.5mm	☐ 3.0mm ☐ 3.5mm
Limiter, Ext	mm	mm
Stroke	mm	mm
Eyelet	☐ Std ☐ +2mm	☐ Std ☐ +2mm
Spring		
Spring Cup	☐ Low ☐ Mid ☐ High	☐ Low ☐ Mid ☐ High

Electronics	
Radio	ESC
Servo	Thro Prof
Battery	Timing Adv
Battery Wt	g Initial Brake
Motor	Drag Brake
Gearing	/ Thr/Bra EPA /

☐ 19g
☐ 26g
☐ 37g

☐ Carbon
☐ Brass

☐ Standard
☐ Stiffezel

☐ Standup
☐ Laydown

☐ Soft
☐ Standard
☐ Stiffezel

☐ Standard
☐ Stiffezel

☐ 1
☐ 2
☐ 3
☐ 4
☐ 5
☐ Carbon

☐ 16g
☐ 25g

☐ Aluminum
☐ Brass, 22g

☐ Standard
☐ Stiffezel

mm Spacer

Total Weight: g Fr/Rr %