

Front Suspension:

Reset Forms

Ride Height:	17mm
Camber:	2gr
Toe:	+0,5
Anti-Roll Bar:	N/A
Arm Type:	Hard/Gull
Tower Type:	Gull
Wheel Hex:	5mm
Steering Block:	4mm
Caster Block Insert:	5gr
Bulkhead Type:	brass
Kick-Up Angle:	25gr
Notes:	Bellcrank +3mm 6.3

Bump Steer Spacing: 1mm

Steering Plate: +2m

Steering Stop Spacing: -

Caster Block Spacing: back

Axle Height:

+3	<input type="checkbox"/>
+2	<input checked="" type="checkbox"/>
+1	<input type="checkbox"/>
+0	<input type="checkbox"/>

Ball Stud Spacing: 1mm

Steering Bellcrank Position:

Up ☐

Down ☒

Ball Stud Spacing: 1mm

B A

R-1

C B A

Rear Suspension:

Ride Height:	17	
Camber:	2	
Anti-Roll Bar:	-	
Arm Type:	hard75mm	
Tower Type:	Stock	
Arm Spacing:	2mm bhnid	
Wheel Hex:	5mm	
Shock Mounting Position:		
Front of Arm <input checked="" type="checkbox"/>	Rear of Arm <input type="checkbox"/>	
Hub Spacing: Fwd <input type="checkbox"/>	Mid <input checked="" type="checkbox"/>	Back <input type="checkbox"/>
CVA Bone Length:	atock	
CVA Axle Type:	stock	
Notes:		

C Mount:

Aluminum ☒ Brass ☐

D Mount:

Aluminum ☒ Brass ☐

Axle Height:

▼0	3▲	+3
▼1	2▲	+2
▲1	2▼	+1
▲0	3▼	+0

Camber Link Spacing: 3mm

Ball Stud Spacing: 2mm

Ball Stud Spacing: 2mm

CBA

Electronics:

Radio:	Sanwa M17	Servo:	Reedy RT3507A
EPA: Throttle:	100 %	Brake:	100 %
ESC:	rEEDY 610r		
ESC Settings:	-		
Motor / Wind:	rEEDY 7,0	Timing:	30
Pinion:	20	Spur:	81
Battery:	Reedy 4800mHa		
Battery Position:			
Back 1 <input type="checkbox"/>	2 <input type="checkbox"/>	3 <input checked="" type="checkbox"/>	4 <input type="checkbox"/> 5 <input type="checkbox"/> Forward
Battery Weight:	+ 50gr		

Drivetrain:

Transmission:	
Laydown: <input checked="" type="checkbox"/>	Layback: <input type="checkbox"/>
Differential:	Ball Diff: <input type="checkbox"/>
Height: 2	Gear Diff: <input checked="" type="checkbox"/>
Diff Setting:	4gear. 6000w
Notes:	

Slipper Clutch:

Type:	stock
# of Pads:	
Setting:	

Shocks:

	Front	Rear
Piston:	2, 1,7	2,1,7 + 1x 1,5
Thickness:	2mm	2mm
Fluid:	40w	30w
Spring:	V2 Purpel	V2 Blue
Limiters:	Int: - Ext: -	Int: - Ext: -
Stroke:	20,5mm	28mm
Eyelet Length:	+2	0
Cup Offset:	5mm	0
Notes:	Kaschima 13mm	



Track Info:

Size:	Small <input type="checkbox"/>	Medium <input type="checkbox"/>	Large <input type="checkbox"/>	Extra Large <input checked="" type="checkbox"/>
Surface:	Dirt <input type="checkbox"/>	Carpet <input type="checkbox"/>	Astroturf <input type="checkbox"/>	Multi Surface <input checked="" type="checkbox"/>
Traction:	Low <input type="checkbox"/>	Medium <input type="checkbox"/>	High <input type="checkbox"/>	Very High <input checked="" type="checkbox"/>
Moisture:	Dry <input type="checkbox"/>	Damp <input type="checkbox"/>	Wet <input checked="" type="checkbox"/>	
Condition:	Indoor <input type="checkbox"/>	Outdoor <input type="checkbox"/>	Dusty <input type="checkbox"/>	Hard Packed <input checked="" type="checkbox"/>
	Bumpy <input checked="" type="checkbox"/>	Grooved <input type="checkbox"/>	Smooth <input type="checkbox"/>	Loamy <input type="checkbox"/>
Temperature:	Ambient: 20gr	Track:		
Notes:	extrem bumpy			
Vehicle Comments:				

Tires:

Front Tires:	handout Cutstagger
Front Compound:	yelow
Front Insert:	
Rear Tires:	Handout / Mezzo
Rear Compound:	yelow
Rear Insert:	
Wheel (F/R):	
Notes:	

Body, Weight:

Body:	S"
Front Wing:	stock
Rear Wing:	stock
Wing Angle:	-
Chassis Length:	+3mm
Servo Weights:	Steel
Electronic Weights:	Steel
Total Vehicle Weight:	1535g